GENATA

ITOONER
Idea Transmission Navigator

AI PoE Switch

GNT-ES06ED-P

- Total 65W Power Supply
- 4 ports PoE
- 2 ports Uplink

Product Features

- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power
- AC cable intergrated with main body, compact in size

Ports Description



1 100Mbps PoE Ports
2 bt 60W Power Ports
3 100Mbps Uplink Ports

Dimension (mm)



Installation Diagram



Specifications

Model	GNT-ES06ED-P
Ports	PoE (1~3):10/100Mbps PoE ports (RJ45) PoE (4):10/100Mbps PoE port (RJ45),Support bt 60W High Power LAN (5~6):10/100Mbps uplink ports (RJ45)
Transmission Rate	10/100Mbps: Full Duplex / Half Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:1.2Gbps
	Network Latency (10 to 100Mbps): ≦16μs (use the 64byte package size)
	MAC address table: 2K
	Packet Forwarding Rate: 0.9Mpps
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total≤65W AI Watchdog: Port 1~4 Power Output: PoE1~3 Port:1/2(+52V),3/6(GND)≤30W PoE 4 Port:1245(+52V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 190mm*80mm*36mm, Weight: 0.5KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC cable intergrated with main body, User Manual

※Specifications subject to change without notice.